



EN 14351-1:2006 +A1:2009

NorDan SP.z o.o

UL. Fabryczna 16
64-200 Wolsztyn
Poland



www.nordan.no

Edition: February 2010

TA-Villa Side Hung
TD- Villa side swing reversible

TG/TY- Villa top swing reversible (classic/ opus)

TE-Villa Balcony door (security)
TX-Villa double balcony door (security)

Reference size for windows: 1230 x 1480

Reference size for doors: 1480 x 2180

Doors are with insulated panel height 1001 mm

Essential performance characteristics

ID	Characteristic	TA	TD	TG/TY	TE	TX
1	Resistance to wind load Test pressure (EN 12210)	Class 3	Class 3	Class 3	Class 3	Class 3
2	Resistance to wind load Frame deflection (EN 12210)	Class C	Class C	Class C	Class C	Class C
5	Watertightness (EN 12208)	Class 9A	Class 9A	Class 9A	Class 9A	Class 9A
8	Impact resistance (EN 13049)	npd	npd	Npd	npd	npd
9	Load-bearing capacity of safety devices (EN 14609)	Passed	Passed	Passed	Passed	Passed
10	Sound insulation (EN ISO 140-3)	npd	npd	npd	npd	npd
11	Thermal transmittance (EN ISO 10077-1)	1,2 W/(m ² K) ¹⁾	1,2 W/(m ² K) ¹⁾	1,2 W/(m ² K) ¹⁾	1,2 W/(m ² K) ¹⁾	1,2 W/(m ² K) ¹⁾
12	Solar energy transmission (EN 410)	48 %	48 %	48 %	48 %	48 %
13	Light transmission (EN 410)	70 %	70 %	70 %	70 %	70 %
14	Air permeability (EN 12207)	Class 4	Class 4	Class 4	Class 4	Class 4
15	Operating forces (EN 13115)	Class 2	Class 2	Class 2	Class 2	Class 2

npd = no performance determined

1) = With Insulated Glass Unit: 6+16G+ES4